

169-60509

HellermannTyton



Article Number: 169-60509

Description: Convoluted Tubing, Slit, .25" Dia, PE, Black, 3200 ft/carton

| | | |
|--------------------|-----------------------------|---|
| Base Data | | |
| | Local Order Number | CTP140STD |
| | Type | CTP140 |
| | Color | Black (BK) |
| | Features and Benefits | <ul style="list-style-type: none"> • Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires. |
| | Quantity Per | carton |
| | Product Description | HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. |
| | Technical Description | Convoluted Tubing, Slit, 1/4" Dia., PE, Black |
| | Short Description | Convoluted Tubing, Slit, .25" Dia, PE, Black, 3200 ft/carton |
| Product Dimensions | | |
| | Length L (Imperial) | 3200.0ft |
| | Length L (Metric) | 975.4m |
| | Inner Diameter D (Imperial) | 0.276" |
| | Inner Diameter D (metric) | 7.01mm |
| | Diameter D (imperial) | 0.398" |
| | Diameter D (metric) | 10.11mm |
| | Diameter D2 (imperial) | 0.276" |
| | Diameter D2 (metric) | 7.01mm |
| | Diameter D3 (metric) | 7.01mm |

169-60509

HellermannTyton

| | | |
|-----------------------------|-------------------------------|----------------------------------|
| Product Dimensions | Outside Diameter D (imperial) | 0.398" |
| | Outside Diameter D (metric) | 10.11mm |
| | Nominal Diameter (Imperial) | 1/4" |
| | Nominal Diameter (Metric) | 6.35mm |
| | Wall Thickness WT (Imperial) | .004" |
| | Wall Thickness WT (Metric) | 0.102mm |
| Material and Specifications | | |
| | Material | Polyethylene (PE) |
| | Material Shortcut | PE |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +199°F (-40°C to +93°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 3200ft |
| | Package Quantity (Metric) | 975.4m |
| | Customs Number(Schedule B) | 3926909987 |