



SPECIFICATION
MATERIALS:
 HOUSING & INSERT: PBT YELLOW
 COUPLING: BRASS-NICKEL PLATED
 O-RING: VITON
ELECTRICAL:
 VOLTAGE: 10-30VDC
 CURRENT RATING: 4A PER PORT, 12 AMPS MAX.
 PROTECTION CLASS: IP67
 OPERATING TEMPERATURE: -5°C to +90°C

NOTES:
 FIXING HOLES TO SUIT M4 SCREWS

DESCRIPTION EC NO: WEU2010-0450 DRWN: REISSNER 2010/03/19 CHKD: FP APPR: NSTAUDIG 2010/03/23	QUALITY SYMBOLS ▽ = 0 ◻ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 1:1	DESIGN UNITS METRIC		THIRD ANGLE PROJECTION		
		4 PLACES	±---	±---	DRAWN BY	DATE	MICRO-CHANGE MPIS 8 PORT TOP MOUNT CABLE PUR				
		3 PLACES	±---	±---	REISSNER	2010/03/19					
		2 PLACES	±---	±---	CHECKED BY	DATE	MOLEX INCORPORATED				
1 PLACE	±0.3	±---	NS	2010/03/19							
ANGULAR ± --- °		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY NSTAUDIG 2010/03/23		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-120114-076		SHEET NO. 1 OF 1	
1		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							