

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	G1		REVISED PER ECO-11-005140	28MAR11	RK	HMR

① [-Z-]面より2mmの範囲で測定。  
 2. 適用プリント基板厚: 1.6mm  
 3. 嵌合相手ハウジング型番: 174046, 174047  
 4. 推奨取付けねじ: JIS B1115, B1122 タッピングねじ, なべ2種  
 呼び径3, 長さ7mm以上 (締付けトルク: 0.4N-m以下)  
 5. 製品規格番号: 108-5244, 取扱説明書: 411-5883  
 ⑥ 回路番号: FIG.1 参照

① TO BE MEASURED WITHIN 2mm FROM [-Z-]  
 2. APPLICABLE P.C.BOARD THICKNESS: 1.6mm  
 3. THE MATING PLUG HOUSING PART NUMBER: 174046, 174047  
 4. RECOMMENDED MOUNTING SCREW: 3mm DIA, 7mm LENGTH (MIN.)  
 PAN HEAD, CLASS 2 TAPPING SCREW SPECIFIED IN JIS B1115,  
 B1122 (TIGHTENING TORQUE: 0.4N-m MAX.)  
 5. PRODUCT SPECIFICATION: 108-5244  
 INSTRUCTION SHEET: 411-5883  
 ⑥ CIRCUIT NUMBER: SEE FIG.1

⑥ FIG.1

プリント基板取付け寸法 (公差 ±0.1)  
 MOUNTING DIMENSIONS FOR P.C.BOARD ; TORERANCE ±0.1  
 \*ピッチは累積しないこと  
 \*NON ACCUMULATE PITC TOERLANCE

TOLERANCE UNLESS OTHERWISE SPECIFIED:  
 一般公差  
 0 < x ≤ 10 : ±0.2  
 10 < x ≤ 30 : ±0.25  
 30 < x ≤ 100 : ±0.3  
 角度 : ±3°

OBSOLETE	SELECTIVE-TIN	PRE-TIN	-	BLACK	2-174146-2
	TIN-LEAD	SELECTIVE GOLD	1~36	BLACK	1-174146-2
		PRE-TIN	-	GREEN	174146-4
		PRE-TIN × 35	-	BLACK	174146-3
	TIN-LEAD	SELECTIVE GOLD × 1	21	BLACK	174146-2
		PRE-TIN	-	BLACK	174146-2
		PRE-TIN	-	WHITE	174146-1
	CONTACT FINISH 半田付け部	CONTACT SIDE 接触部側	GOLD PLATED CIRCUIT NO 金めっき回路番号	COLOR 色	PART NUMBER 製品型番
	CONTACT FINISH コンタクト仕上		⑥		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	T.SHINOHARA	06JAN09
CHK	K.BETSUI	06JAN09
APVD	K.BETSUI	06JAN09

TE Connectivity

040 SERIES MULTI-LOCK I/O CONNECTOR  
 36POSITION CAP HOUSING ASSEMBLY

SIZE	A2	CAGE CODE	00779	DRAWING NO	C=174146
WEIGHT	17.5 g	SCALE	2:1	SHEET	1 of 1
MATERIAL	HOUSING: PBT CONTACT: BRASS	FINISH	SEE TABLE	CUSTOMER DRAWING	REV G1

1471-9 (3/11)

174146

A