

595-44400

HellermannTyton

Article Number: 595-44400

Description: Dot Matrix Label, 1.875' x 1.875", 1 Across, Polyester, White, 5000/pkg



| | | |
|--------------------|-----------------------------------|---|
| Base Data | | |
| | Local Order Number | TAG44-400 |
| | Type | TAG44 |
| | Color | White (WH) |
| | Features and benefits | <ul style="list-style-type: none"> • Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system. |
| | Quantity Per | pack |
| | Product Description | Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements. |
| | Short Description | Dot Matrix Label, 1.875' x 1.875", 1 Across, Polyester, White, 5000/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 1.875" |
| | Length L (Metric) | 47.62mm |
| | Width W (Imperial) | 1.875" |
| | Width W (Metric) | 47.5mm |
| | Height H (Imperial) | 1.875" |
| | Height H (Metric) | 47.5mm |
| | Height of printable area (metric) | 47.50mm |
| | Horizontal Repeat HR (metric) | 47.82mm |
| | Horizontal Repeat HR (imperial) | 1.875" |
| | Print Method | Dot-Matrix |
| | Vertical Repeat VR (imperial) | 2.0" |
| | Vertical Repeat VR (metric) | 50.80mm |
| | Width of Liner WL (imperial) | 2.875" |

595-44400

HellermannTyton

| | | |
|-----------------------------|---------------------------------|-----------------------------------|
| Product Dimensions | Width of Liner WL (metric) | 73.02mm |
| Material and Specifications | | |
| | Material | Type 400, Polyester, white (WH) |
| | Material Shortcut | 400 |
| | Adhesive | Acrylic |
| | Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| | Minimum Application Temperature | from +50°F (from +10°C) |
| | Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL-Recognized |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 5000 |
| | Package Quantity (Metric) | 5000 |
| | Customs Number(Schedule B) | 3919905060 |
| | Labels per Row | 1 |