

Article Number: 112-52109



Description: Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIR,

Black, 1000/pkg

Base Data		
	Local Order Number	CTT60R0HIRM4
	Туре	CTT60R
	Color	Black (BK)
	Features and Benefits	 High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. Head design contains clamping rails to provide full circumferential compression around bundles. Bent tail allows for quick insertion into head.
	Quantity Per	bag
	Product Description	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIR, Black, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	60.0lbs
	Minimum Tensile Strength (Metric)	265.0N
	Length L (Imperial)	8.0"
	Length L (Metric)	205.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.19"
	Width W (Metric)	4.7mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm

generated on: 4/28/2017

112-52109



		_
Product Dimensions	Bundle Diameter Max. (Imperial)	1.8"
	Bundle Diameter Max. (Metric)	45.0mm
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6, high impact modified (PA66HIR)
	Material Shortcut	PA66HIR
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987

generated on: 4/28/2017