

109-00088

HellermannTyton



Article Number: 109-00088

Description: Q Tie, 4.1" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg

| | | |
|--------------------|-------------------------------------|---|
| Base Data | | |
| | Local Order Number | 109-00088 |
| | Type | Q18R |
| | Color | Black (BK) |
| | Features and Benefits | <ul style="list-style-type: none"> • Open-head design with easily detectable slot opening allows for swift and easy insertion • Pre-lock feature allows for a temporary hold • The large ribbed tail permits an ergonomic installation • Two rails on the strap ensure guidance through the cable tie head |
| | Quantity Per | bag |
| | Product Description | Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools. |
| | Short Description | Q Tie, 4.1" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg |
| Product Dimensions | | |
| | Minimum Tensile Strength (Imperial) | 18.0lbs |
| | Minimum Tensile Strength (Metric) | 80N |
| | Length L (Imperial) | 4.1" |
| | Length L (Metric) | 105mm |
| | Fixation Method | None |
| | Identification Plate Position | none |
| | Releasable Closure | No |
| | Tie Closure | plastic pawl |
| | Variant | Inside Serrated |
| | Width W (Imperial) | 0.1" |
| | Width W (Metric) | 2.6mm |
| | Bundle Diameter Min. (Imperial) | 0.06" |

109-00088

HellermannTyton

| | | |
|-----------------------------|---------------------------------|--|
| Product Dimensions | Bundle Diameter Min. (Metric) | 2.0mm |
| | Bundle Diameter Max. (Imperial) | 0.9" |
| | Bundle Diameter Max. (Metric) | 24.0mm |
| | Thickness T (Imperial) | 0.039" |
| | Thickness T (Metric) | 1.0mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 heat stabilized (PA66HS) |
| | Material Shortcut | PA66HS |
| | Flammability | UL 94 V2 |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL ANSI/UL 62275 |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 100 |
| | Package Quantity (Metric) | 100Pieces |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |