

169-60017



Article Number: 169-60017

Description: Convoluted Tubing, Slit, .63" Dia, PA6, Black with Gray Stripe, 800 ft/carton

| | | |
|-------------------------------|-----------------------|--|
| Base Data | Local Order Number | CTN580STD |
| | Type | CTN580 |
| | Color | Black with Gray Stripe (BKSTGY) |
| | Features and Benefits | <ul style="list-style-type: none"> • Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight |
| | Quantity Per | carton |
| | Product Description | HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. |
| | Technical Description | Convoluted Tubing, Slit, 5/8" Dia., PA6, Black w/Gray Stripe |
| | Short Description | Convoluted Tubing, Slit, .63" Dia, PA6, Black with Gray Stripe, 800 ft/carton |
| | Product Dimensions | Length L (Imperial) |
| Length L (Metric) | | 243.8m |
| Inner Diameter D (Imperial) | | 0.639" |
| Inner Diameter D (metric) | | 16.23mm |
| Diameter D (imperial) | | 0.837" |
| Diameter D (metric) | | 21.26mm |
| Diameter D2 (imperial) | | 0.639" |
| Diameter D2 (metric) | | 16.23mm |
| Outside Diameter D (imperial) | | 0.837" |
| Outside Diameter D (metric) | | 21.26mm |
| Nominal Diameter (Imperial) | | 5/8" |

169-60017

HellermannTyton

| | | |
|-----------------------------|------------------------------|-----------------------------------|
| Product Dimensions | Nominal Diameter (Metric) | 15.88mm |
| | Wall Thickness WT (Imperial) | .005" |
| | Wall Thickness WT (Metric) | 0.127mm |
| Material and Specifications | | |
| | Material | Polyamide 6 (PA6) |
| | Material Shortcut | PA6 |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 800ft |
| | Package Quantity (Metric) | 243.8m |
| | Customs Number(Schedule B) | 3926909987 |