

## SUMMARY

### # Wires

Low	26
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Series	C
Termination type	Male solder
IP rating	50
Cable Ø	5.30 - 7.20 mm
Matching parts	
Status	
Alternative part	



*Image is for illustrative purpose only*

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	CA*: Straight plug with cable collet and nut for fitting a bend relief
Keying	
Housing Material	PSU (Polysulfone), gray
Cable Fixing	∅ 5.3 - 7.2 mm
Variant	

### Performance

Configuration	
Insulator	
Rated Current	2 Amps

### Specifications

Test voltage (kV rms) Contact-contact:	1
Air clearance min. (mm) or Creepage distance min. (mm):	0.55

### Others


F ret (min):	150 N
--------------	-------

F ret (max): 250 N  
R leak (He) (max): 0.000001 mbar\*l/s (if vacuum-tested)  
Steam sterilization: 20 times (with potting on rear connection)  
IP Rating: 50

---

## DRAWINGS

### Draws



### Dimensions

	A	L
mm.	18	57
in.	0,71	2,24

---

## RECOMMENDED BY LEMO

### Tools

None

### Cables