

## Socket terminal block - JBC 2,5/3 - 3240164

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



3-pos. socket terminal block with spring-cage connection, for toolless wiring with push-in connection method, for one and multi-strand conductors with a cross section of 0.5 to 2.5 mm<sup>2</sup>, insulation housing transparent.

### Product Features

- ✔ Thanks to Push-in connection technology, the three junction box connector versions from Phoenix Contact enable tool-free wiring in a small amount of space
- ✔ Different cross sections can be wired together in a junction box connector
- ✔ Solid multi-strand conductors (7 litz wires) with a cross section range of 1.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup> can be safely connected
- ✔ Solid single-strand conductors with a cross section range of 0.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup> can be connected
- ✔ The transparent housing makes it easier to carry out a visual inspection of the terminal points, thereby increasing wiring safety
- ✔ Integrated test openings enable the use of test devices once wiring has been completed

### Key commercial data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	0.016 GRM
Custom tariff number	85369010
Country of origin	Austria

### Technical data

#### General

Number of levels	1
Number of connections	3
Color	transparent
Insulating material	PC/PA
Inflammability class according to UL 94	V2
Maximum load current (lower level)	24 A
Nominal current I <sub>N</sub> (lower level)	24 A
Nominal voltage U <sub>N</sub>	450 V
Maximum load current (upper level)	24 A

# Socket terminal block - JBC 2,5/3 - 3240164

## Technical data

### General

Number of positions	3
---------------------	---

### Dimensions

Width	17.2 mm
Length	15.6 mm
Height	8.9 mm

### Connection data

Connection method	Push-in connection
Conductor cross section solid min.	0.5 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max.	14
Conductor cross section stranded min.	1.5 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Min. AWG conductor cross section, stranded	16
Max. AWG conductor cross section, stranded	14
Stripping length	8 mm

## Classifications

### eCl@ss

eCl@ss 4.0	27141104
eCl@ss 4.1	27141104
eCl@ss 5.0	27141104
eCl@ss 5.1	27141104
eCl@ss 6.0	27141106
eCl@ss 7.0	27141106
eCl@ss 8.0	27141106

### ETIM

ETIM 3.0	EC001284
ETIM 4.0	EC001284
ETIM 5.0	EC000446

### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703

# Socket terminal block - JBC 2,5/3 - 3240164

## Classifications

### UNSPSC

UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

## Approvals

### Approvals

---

#### Approvals

GOST / GOST / UL Listed

---

#### Ex Approvals


---


Approvals submitted

---

## Approval details

GOST 
--

GOST 
--

UL Listed 	
mm <sup>2</sup> /AWG/kcmil	20-16
Nominal current I <sub>N</sub>	20 A
Nominal voltage U <sub>N</sub>	600 V

---