

169-60503

# HellermannTyton



Article Number: 169-60503

Description: Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 150ft/carton

Base Data		
	Local Order Number	CTP1120STD
	Type	CTP1120
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.</li> <li>• Tubing provides full coverage where spiral wrap or other coverings may not be suitable.</li> <li>• In harsh applications the tubing provides resistance to crushing, impact, and abrasion.</li> <li>• Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.</li> </ul>
	Quantity Per	carton
	Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
	Technical Description	Convoluted Tubing, Slit, 1-1/2" Dia., PE, Black
	Short Description	Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 150ft/carton
Product Dimensions		
	Length L (Imperial)	150.0ft
	Length L (Metric)	45.7m
	Inner Diameter D (Imperial)	1.647"
	Inner Diameter D (metric)	41.83mm
	Diameter D (imperial)	1.947"
	Diameter D (metric)	49.45mm
	Diameter D2 (imperial)	1.647"
	Diameter D2 (metric)	41.83mm
	Outside Diameter D (imperial)	1.947"

169-60503

**HellermannTyton**

Product Dimensions	Outside Diameter D (metric)	49.45mm
	Nominal Diameter (Imperial)	1-1/2"
	Nominal Diameter (Metric)	38.10mm
	Wall Thickness WT (Imperial)	.006"
	Wall Thickness WT (Metric)	0.152mm
Material and Specifications		
	Material	Polyethylene (PE)
	Material Shortcut	PE
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +199°F (-40°C to +93°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	150ft
	Package Quantity (Metric)	45.72m
	Customs Number(Schedule B)	3926909987