


A




Extended length is with 500g of force

B

C

D



SEC:A-A

TERMINATION:

P1	COLOR
1	BLACK
2	RED
3	GREEN
4	YELLOW

Extended Length ("L2")	Typical Retracted Length ("L1")
300.0 Inches - 345.0 Inches	75.0 Inches
7,620.0MM-8,763.0MM	1,905.0MM

Material:

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[0.14MM] Thick Phosphor Bronze
- Connector: 50µ" of Selective Gold Contact Plating
 - Area, Gold flash over the remainder
 - Over 2.54µm[.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X4C): PP6331 ID 0.95-1.0
- Jacke: PVC No UL 80 P
- Package: Individual PE Bag

G

Scale	1:1						Name
TOLERANCE						Drawn	11.02.11 Chappell
X.X	±0.40					Approved	
X.XX	±0.25						
X.XXX	±0.15						
Angle	±3°						
Modification			Date	Name			



Item No.	AT-C-26-4/4/B-25-OE
Title	NON-UL 26AWG (0.12X12)*4C, O.D.: 2.4*4.8MM, Single Plug, 50µ" of contact plating, BLACK
Drawing No.	rev00
Replace	Sheet

H