

Housing - HC-B 6-KML-73/O1M20 - 1604719


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HEAVYCON coupling housing B6, with single locking latch, height 73 mm, with support 1x M20



Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 881634
Custom tariff number	85389099
Country of origin	GERMANY

Technical data

General data

Note	For contact inserts HC-B6, BB10, DD24, M
Design	B6
Height	73 mm
Width	43 mm
Length	60 mm
Housing type	Coupling housings
Locking type	With single locking latch
No. of cable exits	1
Cable exit	Straight
Type of the screw connection	1x M20
Degree of protection for housing	IP65
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR

Housing - HC-B 6-KML-73/O1M20 - 1604719

Technical data

General data

Material lock	Stainless steel, handle: PA
Material grip body interlock	PA-GF

Classifications

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502
UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Housing - HC-B 6-KML-73/O1M20 - 1604719

Approvals

Approval details



Drawings

Dimensioned drawing

