

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set consisting of: 1407729, 1407730, 1407634, 1407628, 1407670

Product Features

- Lower costs than metal version
- Labeling option using 9 x 20 mm marking label
- Low weight
- Lower risk of condensation
- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Halogen-free plastic
- Impact test according to IK 08
- Marking label can be attached



Key Commercial Data

Packing unit	1 pc	
Weight per Piece (excluding packing)	360.0 g	
Custom tariff number	85366990	
Country of origin	Germany	

Technical data

General

Number of positions	10+PE	
Туре	B10	
Connection method	Push-in connection	
Cable exit	straight	



Technical data

General

Degree of protection for housing	IP66	
	4 (UL50e / NEMA 250)	
	4X (UL50e / NEMA 250)	
	12 (UL50e / NEMA 250)	
Connection method	Push-in connection	
Rated voltage (III/3)	500 V	
Rated surge voltage	6 kV	
Rated current	16 A	

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Articles in set

Contact insert - HC-B 10-I-PT-F - 1407729



HEAVYCON socket insert, B10 series, 10 + PE-pos., push-in connection

Contact insert - HC-B 10-I-PT-M - 1407730



HEAVYCON pin insert, B10 series, 10 + PE-pos., push-in connection

Housing - HC-EVO-B10-BWD-PLRBK - 1407634



HEAVYCON EVO panel mounting base, plastic, B10, with double locking latch, height: 30.5 mm, with flat gasket



Articles in set

Housing - HC-EVO-B10-HLFD-PLBK - 1407628



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B10, for double locking latch, height: 60.5 mm, without EVO screw connection

Cable gland - HC-B-G-M25-PLRBK - 1407670



EVO plastic cable gland with bayonet locking, for housing series B, size M25, cable diameter: 9 ... 17 mm

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202

ETIM

ETIM 3.0	EC000438
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522



Approvals		
Approvals		
Approvals		
EAC / EAC		
Ex Approvals		
Approvals submitted		
Approval details		
EAC		
EAC		
Drawings		
Sch	ematic diagram	Schematic diagram
	⊕ 6	1 0 0 6 2 0 0 7 3 0 0 8 4 0 0 9 5 0 0 10


Pin assignment, connection side, pin

Pin assignment, connection side, socket




Derating diagram

Dimensional drawing



Dimensional drawing

Dimensional drawing



Panel cutout

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com