

Electronic housing - EMG100-LG/MSTB - 2907570

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Electronic housing, for PCB insertion, without screw connection terminal blocks and cover, with lateral opening for connector

Product Features

- High degree of flexibility due to the wide choice of versions
- Space-saving accommodation of electronic components in finely graded module versions available with 10 to 150 mm pitch
- Uniform and appropriate housing technology
- User-friendly and safe mounting on DIN rails according to EN 60715
- ☐ Inflammability class V0 insulation material (according to UL 94)
- Shock and contamination-proof accommodation of electronic components
- Universal PCBs for all pitches



Key commercial data

| Packing unit | 1 pc |
|--------------------------------------|-----------|
| Weight per Piece (excluding packing) | 78.48 GRM |
| Custom tariff number | 85472000 |
| Country of origin | Germany |

Technical data

General

| Housing type | Component housing |
|------------------|--------------------------------|
| Housing material | Polycarbonate fiber reinforced |
| Color | green |

Ambient conditions

| Ambient temperature (operation) | -40 °C 125 °C |
|---------------------------------|---------------|



Electronic housing - EMG100-LG/MSTB - 2907570

Technical data

Dimensions

| Length | 75 mm |
|-----------------------|---------|
| Constructional height | 47.5 mm |
| Width | 100 mm |

Technical data

| Inflammability class according to UL 94 | V0 |
|---|--------------------|
| Power dissipation at 20°C in the horizontal mounting position | 6.9 W 7.8 W 7.5 mm |
| | 8 W 8.4 W 15 mm |
| | 8.9 W 9.8 W 52 mm |

Connection data

| Conductor cross section solid min. | 0.2 mm² |
|--|---------|
| Conductor cross section solid max. | 4 mm² |
| Conductor cross section stranded min. | 0.2 mm² |
| Conductor cross section stranded max. | 2.5 mm² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |

Classifications

eCl@ss

| eCl@ss 4.0 | 27180401 |
|------------|----------|
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |

ETIM

| ETIM 2.0 | EC001031 |
|----------|----------|
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC000886 |

UNSPSC

| UNSPSC 6.01 | 31261501 |
|---------------|----------|
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |



Electronic housing - EMG100-LG/MSTB - 2907570

Classifications

UNSPSC

| UNSPSC 12.01 | 31261501 |
|--------------|----------|
| UNSPSC 13.2 | 31261501 |

Approvals

Approvals

Approvals

GOST

Ex Approvals


Approvals submitted

Approval details


GOST 🕑

Drawings

Dimensioned drawing



Dimensioned drawing



^{1 =} Top edge of the PCB

B = Housing width



Phoenix Contact 2014 © - all rights reserved http://www.phoenixcontact.com