

170-22000



Article Number: 170-22000

Description: Helagaine Braided Sleeving, 20 mm Dia, PA66, GY, 164ft/Reel

| Base Data | |
|---------------------------------|---|
| Local Order Number | 170-22000 |
| Type | HEGPA6620 |
| Color | Gray (GY) |
| Features and Benefits | <ul style="list-style-type: none"> • Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture. • Material performs well in wet applications and where abiding substrate has a smooth surface. |
| Quantity Per | metre |
| Product Description | Helagaine Nylon Polyamide Expandable Braided Sleeving is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion. |
| Short Description | Helagaine Braided Sleeving, 20 mm Dia, PA66, GY, 164ft/Reel |
| Product Dimensions | |
| Length L (Imperial) | 164.0ft |
| Length L (Metric) | 50.0m |
| Reel Length (imperial) | 164.0ft |
| Bundle Diameter Min. (Imperial) | 0.59" |
| Bundle Diameter Min. (Metric) | 15mm |
| Bundle Diameter Max. (Imperial) | 0.91" |
| Bundle Diameter Max. (Metric) | 23mm |
| Diameter D (imperial) | 0.79" |
| Nominal Diameter (Imperial) | 3/4" |
| Nominal Diameter (Metric) | 20mm |
| Material and Specifications | |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |

170-22000



| | | |
|-----------------------------|------------------------------|-----------------------------------|
| Material and Specifications | Flammability | UL 94 V2 |
| | Halogenfree | Yes |
| | Operating Temperature | -76°F to +302°F (-60°C to +150°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| | Certification/Specification | EN 45545: 2013 |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 164ft |
| | Package Quantity (Metric) | 50m |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | metre |
| | Weight (Metric) | 1.4kg |