

596-00625

HellermannTyton

Article Number: 596-00625

Description: Thermal Transfer Labels, Self-Laminating, 1.0" x .75" x 2.25", 1 across, VL, White, 1000/roll



Base Data	
Local Order Number	596-00625
Type	TAG2T1-100B
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Thermal transfer labels are made with high performance materials for long term industrial applications. • Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. • The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Quantity Per	reel
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3 cardboard core."
Short Description	Thermal Transfer Labels, Self-Laminating, 1.0" x .75" x 2.25", 1 across, VL, White, 1000/roll
Product Dimensions	
Width W (Imperial)	0.5"
Width W (Metric)	12.7mm
Height H (Imperial)	0.5"
Height H (Metric)	12.7mm
Height H2 (Imperial)	1.43"
Height H2 (Metric)	36.5mm
Bundle Diameter Min. (Imperial)	0.137"
Bundle Diameter Min. (Metric)	3.5mm
Bundle Diameter Max. (Imperial)	0.29"
Bundle Diameter Max. (Metric)	7.6mm
Horizontal Repeat HR (metric)	16.81mm
Horizontal Repeat HR (imperial)	0.66"

596-00625

HellermannTyton

Product Dimensions	Print Method	Thermal transfer
	Thickness T (Metric)	25µm
	Vertical Repeat VR (imperial)	1.62"
	Vertical Repeat VR (metric)	41.28mm
	Width of Liner WL (imperial)	1.0"
	Width of Liner WL (metric)	25.4mm
Material and Specifications		
	Material	Vinyl
	Material Shortcut	VL
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	ROHS Compliant	Yes
Certification/Specification	UL-Recognized	
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3919102055
	Labels per Row	1