

111-32110

HellermannTyton



Article Number: 111-32110

Description: Extended-Long Tie, POM, Black, 10-27" straps and 10 heads/pkg

Base Data		
	Local Order Number	TELS-27
	Type	TELS-27
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Continuous strap and separate heads allow for any bundle diameter, eliminating waste. • Smooth strap prevents cable damage. • UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.
	Quantity Per	pack
	Product Description	HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.
	Short Description	Extended-Long Tie, POM, Black, 10-27" straps and 10 heads/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	250.0lbs
	Minimum Tensile Strength (Metric)	1112.0N
	Length L (Imperial)	27.0"
	Length L (Metric)	686.0mm
	Fixation Method	2 piece
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	steel pawl
	Variant	Extended Length
	Width W (Imperial)	0.5"
	Width W (Metric)	12.7mm
	Width W2 (Imperial)	0.8"

111-32110

HellermannTyton

Product Dimensions	Width W2 (Metric)	20.3mm
	Height H (Imperial)	0.49"
	Height H (Metric)	12.4mm
	Thickness T (Imperial)	0.06"
	Thickness T (Metric)	1.52mm
Material and Specifications		
	Material	Polyacetal (POM)
	Material Shortcut	POM
	Material Cable Tie	Polyacetal (POM)
	Flammability	UL 94 HB
	Material Head	Polyacetal (POM)
	Material Spacer	Polypropylene, UV-resistant (PPW)
	Minimum Application Temperature	-
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	3926909987