
SERPAC 172Ri (3D exploded)

-Click on image to show toolbar. Use ▶ **||** to Play/Pause Animation. -Left click and drag on image to move 3D model.



Threaded inserts only have to be assembled the first time.

2.00

roofing gasket 7 optional. e note #2

TOP.

i-plate area 6.43" X 4.43"

Non-Textured 0.010" recessed

4.88

a) Zoom in & out with center wheel.

b) Pause at any moment to view and or print views.

c) Change the views to ortho and section views if needed from the Views pull down menu.

d) Explore options included in the tool bar like: Views, Transparency of model, Lighting type, etc.

PART NO.	DESCRIPTION (Included)	ACCSESSORIES (Optional)	
7-2Ri	TOP	PART NO.	DESCRIPTION
17	воттом	PS 17	Perimeter Seal
6018	4-40 SCREW (6)	370	Prototype Grid Circuit Board
6102	THREADED INSERTS (6)	470	Prototype Clad Circuit Board

Enclosure weight .45 lbs / 206 gm

1) Enclosure meets or exceeds IP40 and NEMA 1

2) When used with PS17 the enclosure meets or exceeds IP 67 and NEMA 4X, 12 and 13 MIL-STD-810G 506.5

3) Circuit Board drawings can be download at:

http://www.serpac.com/Accessories/CircuitBoard/drawings/370-470-cbc.pdf 4) All components are RoHS Compliant.

ALL DIMENSIONS ARE ± .010" 7/29/10 (1 of 2) 2009 Wright Ave. La Verne, CA 91750 Ph. (626) 331-0517 Fx. (626) 331-8584 serpac.com

