

151-28602

Article Number: 151-28602

Description: Adhesive Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/SR T50, Black, 100/pkg



Base Data	Local Order Number	MB5A0C2
	Type	MB5A
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • For use with 18 and 30 pound cable ties to provide stability when securing bundles. • Secures with rubber based adhesive backing and/or two or four screws. • 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.
	Quantity Per	bag
	Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
	Short Description	Adhesive Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/SR T50, Black, 100/pkg
Product Dimensions	Length L (Imperial)	1.49"
	Length L (Metric)	37.7mm
	Fixation Method	Screw Mounting and Adhesive
	Width W (Imperial)	1.49"
	Width W (Metric)	37.7mm
	Cable Tie Width Max. (Imperial)	0.35"
	Cable Tie Width Max. (Metric)	8.9mm
	Height H (Imperial)	0.28"
	Height H (Metric)	7.1mm
	Mounting Hole Diameter D (Imperial)	0.19"
	Mounting Hole Diameter D (Metric)	4.8 mm
	Mounting Hole Centers (Imperial)	1.0"

151-28602



Material and Specifications	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Adhesive	Synthetic rubber with base of polyethylene foam
	Adhesive Operating Temperature	-4°F to +122°F (-20°C to +50°C)
	Flammability	UL 94 V2 (excluding adhesive)
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	bag