



1. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
2. MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .068 DIA.
3. STAINLESS STEEL RETENTION CLIPS ARE INCLUDED IN INSERTS
4. PACKAGE STAMPED M 24308/4-32SF
5. THIS PLUG WILL ACCEPT SIZE 20 PIN CONTACT M24308/11 OR AMP # 205089

AMP PART NO. STAMPED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION STAMPED IN THIS AREA.

DO NOT SCALE PRINT. UNLESS SPECIFIED TO THE CONTRARY, DIMENSIONS ARE IN INCHES. 3 PLG DEC # .005. ANGLES 12-10-87	DR 12-8-87 C.C. THOMAS	NAME	AMP
2 PLG DEC # .005. ANGLES 12-10-87	CHK 12-10-87	AMP LITE PLUG FOR PIN CONTACTS	AMP INCORPORATED
3 PLG DEC # .005. ANGLES 12-10-87	APPD 12-10-87	H1-DENSITY "HDM-20" CONNECTOR	MEMPHIS, TN 38125
MATERIAL	APPD 12-10-87	SIZE 2 (15 POSN) SERIES 109	
SEE CALLOUTS	PRODUCT SPEC	WITH FLOAT BUSHINGS	
SEE CALLOUTS	APPLICATION SPEC	SIZE FSN NO	DRAWING NO
	WEIGHT	D 00779	205408
		SCALE 4:1	SHEET 1 OF 1

OBSELETE	BRASS	205408-2
	STEEL PER ASTM-A-109	205408-1
	SHELL MAT'L	PART NO