

Article Number: 318-60154

Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1/2", 12.0/4.0 Dia, PO, Black, 10/pkg Description:

	-	atota .	1
	Hellen	marmiyan	North Windshoot Com

Base Data		
	Local Order Number	318-60154
	Type	TAN33-ST-12/4 BK
	Color	Black (BK)
	Features and Benefits	 Adhesive lining provides an excellent seal against moisture and humidity. 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters, while thin exterior wall is very flexible and provides superior insulation. Meets UL224 VW-1 specifications making it ideal high heat applications (excludes clear tubing). Polyolefin material provides mechanical strength with good resistance to solvents, oils and fuels.
	Quantity Per	pack
	Product Description	TAN33 is a flexible, thin wall adhesive lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity. 4-foot sticks are individually labeled for retail.
	Short Description	Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1/2", 12.0/4.0 Dia, PO, Black, 10/pkg
Product Dimensions		
	Length L (Imperial)	4.0ft
	Length L (Metric)	1.22m
	Printable (Yes/No)	No
	Shrink Ratio	3:1
	Trade Size	1/2 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 ¹⁴ Ω cm
	Nominal Diameter (Imperial)	1/2"
	Nominal Diameter (Metric)	12mm
	Wall Thickness WT (Imperial)	.063"
	Wall Thickness WT (Metric)	1.60mm
	Recovered Diameter d (metric)	4.0mm

4/28/2017 generated on:

318-60154



Recovered Diameter d (imperial)	0.450
toovered Biameter a (impenal)	0.158"
Supplied Diameter D (imperial)	0.472"
Supplied Diameter D (metric)	12.0mm
/laterial	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Elongation at break	400%
lalogenfree	No
Shrink Temperature	+212 °F (+100 °C)
Operating Temperature	-67°F to +257°F (-55°C to +125°C)
ROHS Compliant	Yes
JL Recognized (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number(Schedule B)	3926909987
S	laterial Idaterial Shortcut Iongation at break Ialogenfree Inhrink Temperature Ioperating Temperature Iohs Compliant IL Recognized (US) Idackage Quantity (Imperial) Idackage Quantity (Metric)

generated on: 4/28/2017