

133-00059

Article Number: 133-00059



Description: Cable Tie and Edge Clip, 50 lbs, 3.5" Long, EC5, Panel Thickness .04"-.12", PA66HS, Black, 500/bag

| Base Data | |
|-------------------------------------|--|
| Local Order Number | 133-00059 |
| Type | T40XEC5SP-E |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none"> • Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. |
| Quantity Per | bag |
| Product Description | The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing. |
| Short Description | Cable Tie and Edge Clip, 50 lbs, 3.5" Long, EC5, Panel Thickness .04"-.12", PA66HS, Black, 500/bag |
| Product Dimensions | |
| Minimum Tensile Strength (Imperial) | 40.0lbs |
| Minimum Tensile Strength (Metric) | 178N |
| Length L (Imperial) | 3.5" |
| Length L (Metric) | 85.0mm |
| Fixation Method | Edge Clips |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.16" |
| Width W (Metric) | 4.0mm |
| Width W2 (Imperial) | 0.33" |
| Width W2 (Metric) | 8.3mm |
| Height H (Imperial) | 0.05" |

133-00059



| | | |
|-------------------------------|---------------------------------|--|
| Product Dimensions | Height H (Metric) | 1.2mm |
| | Height H2 (Imperial) | 0.46" |
| | Height H2 (Metric) | 11.6mm |
| | Bundle Diameter Min. (Imperial) | 0.08" |
| | Bundle Diameter Min. (Metric) | 1.6mm |
| | Bundle Diameter Max. (Imperial) | 0.6" |
| | Bundle Diameter Max. (Metric) | 15.0mm |
| | Panel Thickness Max. (Imperial) | 0.12" |
| | Panel Thickness Max. (Metric) | 3.0mm |
| | Panel Thickness Min. (Imperial) | 0.04" |
| Panel Thickness Min. (Metric) | 1.0mm | |
| Material and Specifications | | |
| | Material | Polyamide 6.6 heat stabilized (PA66HS) |
| | Material Shortcut | PA66HS |
| | Flammability | UL 94 V2 |
| | Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500Pieces |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |
| | Weight (Metric) | 1.25kg |